

# LINX 8840 PRINTER



## Low total cost of ownership

- ✓ Solvent consumption as low as 3.5ml\* per hour to save on fluid costs
- ✓ Single part ink and filter change minimising service costs
- ✓ Printhead cleaning interval up to three months to reduce downtime and fluids consumption



## Built-in reliability for increased productivity

- ✓ Unique sealed printhead design protects critical components from physical damage
- ✓ 8 hour reserve print capacity to reduce line stoppages from fluid running empty
- ✓ Linx PrinterNet™ enabled IoT solution gives you better control of your production line and fast remote fault resolution to improve uptime



## Consistent error-free codes and ease of use

- ✓ Customisable touch-screen with your product images to provide error-free code setup without language barriers
- ✓ Fast one-touch access to frequently used functions and step by step guides for right first time set up
- ✓ Simple, one-touch, fluid cartridge refills during printing no mess, no tools, no mistakes

\*average consumption at 20°C, ink and application dependent

**The Linx 8840 continuous ink jet printer prints up to 6 lines and provides a perfect coding solution for industrial environments.**

Designed to reduce your total cost of ownership and increase your production line output, the Linx 8840 delivers consistent, error-free codes.

With its unique sealed printhead design and durable stainless steel construction the Linx 8840 operates reliably in tough production environments, optimising line productivity.



Neeshu Marking & Coding

LINX

# Linx 8840

## PRINTHEAD

60mm minimum bend radius in static applications. 180mm minimum bend radius in dynamic applications.



## SIDE ELEVATION



## FRONT ELEVATION



## 90° PRINTHEAD OPTION



## Technical Specifications

### PRINT SPEEDS AND SIZES

|  |   |   |
|--|---|---|
| Printhead:   | Mk11 Midi                                   | Mk11 Midi plus                              |
| Nozzle size:   | 62 µm                                       | 75 µm                                       |
| Lines of print:  | Up to 6                                     | Up to 6                                     |
| Character height range:                                      | 1.8 to 20 mm                                | 2.1 to 20.1 mm                              |
| Maximum speed for single line print (5 dot high characters): | 7.50 m/s (0.47 mm drop pitch)               | 9.10 m/s (0.57 mm drop pitch)               |
| Maximum speed for two line print (7 dot high characters):    | 2.65 m/s (0.43 mm drop pitch)               | 2.57 m/s (0.52 mm drop pitch)               |
| Recommended distance from printhead to substrate:            | 12mm (35mm for carton coding message style) | 20mm (45mm for carton coding message style) |

### HARDWARE FEATURES

- Easi-Change® Service Module, change interval: up to 18 months (13,000 hours) – dye-based inks, up to 12 months (6,000 hours) – soft pigmented inks\* Only 0.5L of ink changed
- Unique automatic printhead flushing: typical cleaning interval 3 months (100 starts and stops) – dye-based inks, up to 1 month – soft pigmented inks
- Printhead jet-speed control and temperature sensing for consistent printing in changing ambient temperatures
- Mistake-proof, mess-free ink and solvent refilling while printing (0.5 litre ink cartridge, 1 litre solvent cartridge)
- 7-inch full colour touch screen with tough, solvent-resistant polymer cover
- Durable ink pump with no scheduled changes required
- Extended shutdowns (up to 3 months) without printer flushing or draining
- Robust, flexible dual-tube conduit for static and moving printhead applications

### SOFTWARE FEATURES

- Single-press start print, pause print and jet shutdown
- Auto power-off after jet shutdown
- Simple message creation and editing with drag-and-drop field positioning, zoom function and insert mode for long messages
- Total print count, message count and batch count
- Message selection using product images
- Password-protected functions, with customisable user profiles

- Message creation/editing while printing
- On-screen output rate measurement and production stoppage log. Downloadable onto USB device
- On-screen fluid level indicators, 12 hour running from fluid refill warning to printer stop in most applications
- On-screen help and diagnostics information
- QuickSwitch® message selection and editing using bar code scanner
- PrintSync® automatic font and message format selection, based on message style selected and production line speed
- Multiple operator languages (user selectable) with on-screen keyboards, secondary keyboard for multi-language printing
- Simple line speed and shaft encoder setup wizard, for installation on new production lines
- Message store and printer settings backup, copy and restore using USB storage device
- Simple Communications Protocol (YAML based scripts) and Linx Remote Communications Interface for connection to PCs or PLCs using Ethernet port

### MESSAGE PRINTING FACILITIES

- Text, symbols and numbers
- Prompted fields for one-step message editing with customisable on-screen prompts
- Height, width and delay functions for easy code sizing and positioning
- Automatic formats for printing dates, times and date rounding (using the printer's internal clock)
- Custom date and time editor to create different date formats as required
- Automatic date forward function. Add number of seconds, minutes, hours to the current time, or number of days, weeks or months to the current date
- Automatic time adjustment option for daylight savings time
- Sequential numbering, forward and backward counting, variable intervals
- One-touch sequential number reset option from the printer screen, and reset using external trigger
- Number of messages stored: up to 1000 using internal printer memory (depending on message content), more can be stored using a USB storage device
- Bold character printing (up to 9 times)
- Variable character spacing for improved vision system recognition
- Rotated character (tower) printing
- Shift coding (message content changes automatically at defined times)

- Graphics and logos can be imported into the printer as bitmap files using the USB port
- Reverse and inverted printing
- Barcodes (ITF 2 of 5, Code 39, Code 128, EAN 13, EAN 8, UPCA, Pharmacode, Data Matrix, QR Code)

### PRINTHEAD OPTIONS

- 2m conduit
- 4m conduit (option)
- 90° printhead (option)
- Positive air purge to printhead (provides improved reliability in dusty or humid environments) (option)

### INK RANGE

- Linx MEK base (dye-based, soft pigmented-based)
- Linx mixed base (MEK-free, dye-based)
- Linx ethanol base (MEK-free, dye-based)

### SOLVENT CONSUMPTION

3.5ml/hour (at 20°C, ink and application dependent)

### CONNECTIONS/INTERFACING FOR

- Product detector
- Shaft encoder/second product detector
- External single-stage alarm output (24v)
- USB – for message backup and transfer, and wifi connection for Linx PrinterNet
- Ethernet
- Volt-free contact alarm connection (e.g. for use with external mains-driven alarm) (option)
- Dual alarm output (Volt free and 24V output) (option)

### PHYSICAL CHARACTERISTICS

- Base and enclosure: Stainless steel
- IP55 environmental protection rating\*\*
- Mounting options: Static stand, mobile stand, bench, wall mount bracket
- Operating temperature range: 5-45°C (0-50°C for Linx 1240 ink type)
- Humidity range (r.h., non-condensing): 90% max
- Power supply: 100-230V, 50/60Hz
- Power consumption: 38W (typical when printing)
- Power rating: 100 W
- Weight: 24kg (including fluids and printhead)

### REGULATORY APPROVALS

CE, EAC, NRTL, FCC

\*Interval may be adjusted in certain environments and applications to provide reliable running between service module changes

\*\*IP rating is independently verified – certificates available on request



For more information, contact Neeshu Marking & Coding Private Limited, 30, F-2, Mandar Apartment, Khamala Ring Road, Nagpur - 440025, Maharashtra, India.

Contact 9665054081 Email neeshuenterprises@gmail.com, linx@neeshumarking.com Website www.neeshumarking.com

Linx and Easi-Change are registered trademarks of Linx Printing Technologies Ltd. © Linx Printing Technologies Ltd 2019

